

Specifications

Weight

2.2 kg

Counterbalance Weight

0 → 8 kg

Bubble Spirit Level (No.)

1

Safety Payload Weight

8 kg

Certifications

WEEE; RoHS

Colour

Black

Front Tilt

-70° / +90°

Head Type

Video/Fluid Head

Counterbalance System

Variable Continuous

Material

Aluminium

Center Of Gravity

55 mm

Powered By (Batteries)

Lithium

Top Attachment

1/4" screw, 3/8" screw

Easy Link

Yes

Ball Flat

Flat

Maximum Working Temperature

50 °C

Specifications

Weight

2.2 kg

Counterbalance Weight

0 → 8 kg

Bubble Spirit Level (No.)

1

Safety Payload Weight

8 kg

Certifications

WEEE; RoHS

Colour

Black

Front Tilt

-70° / +90°

Head Type

Video/Fluid Head

Counterbalance System

Variable Continuous

Material

Aluminium

Center Of Gravity

55 mm

Powered By (Batteries)

Lithium

Top Attachment

1/4" screw, 3/8" screw

Easy Link

Yes

Ball Flat

Flat

Maximum Working Temperature

50 °C

Specifications

Weight

2.2 kg

Counterbalance Weight

0 → 8 kg

Bubble Spirit Level (No.)

1

Safety Payload Weight

8 kg

Certifications

WEEE; RoHS

Colour

Black

Front Tilt

-70° / +90°

Head Type

Video/Fluid Head

Counterbalance System

Variable Continuous

Material

Aluminium

Center Of Gravity

55 mm

Powered By (Batteries)

Lithium

Top Attachment

1/4" screw, 3/8" screw

Easy Link

Yes

Ball Flat

Flat

Maximum Working Temperature

50 °C

Specifications

Weight

2.2 kg

Counterbalance Weight

0 → 8 kg

Bubble Spirit Level (No.)

1

Safety Payload Weight

8 kg

Certifications

WEEE; RoHS

Colour

Black

Front Tilt

-70° / +90°

Head Type

Video/Fluid Head

Counterbalance System

Variable Continuous

Material

Aluminium

Center Of Gravity

55 mm

Powered By (Batteries)

Lithium

Top Attachment

1/4" screw, 3/8" screw

Easy Link

Yes

Ball Flat

Flat

Maximum Working Temperature

50 °C

Specifications

Weight

2.2 kg

Counterbalance Weight

0 → 8 kg

Bubble Spirit Level (No.)

1

Safety Payload Weight

8 kg

Certifications

WEEE; RoHS

Colour

Black

Front Tilt

-70° / +90°

Head Type

Video/Fluid Head

Counterbalance System

Variable Continuous

Material

Aluminium

Center Of Gravity

55 mm

Powered By (Batteries)

Lithium

Top Attachment

1/4" screw, 3/8" screw

Easy Link

Yes

Ball Flat

Flat

Maximum Working Temperature

50 °C